



Husqvarna DXR 250

The Husqvarna DXR 250 is a remote-controlled demolition robot with a contemporary design, packed with new technology and intelligent features. It is compact and light, yet robust and powerful. It has a fixed arm with a range of 4.8 metres and a width of only 78 cm that enables it to pass through most doorways and stairways are not a problem either. Its low profile body ensures the operator can see over the machine when working, creating a safer and more efficient working environment. The strong, durable baseplate ensures lots of power despite its low weight. The DXR 250 comes standard with practical dozer blades which also function as support. The machine is easily controlled with a very user-friendly remote control. It is perfect for jobs in hard-to-reach spaces, both indoors and out.



Features Husqvarna DXR 250

- Grease pump, automatic greasing system for the tools as standard.
- The DXR 250 has dozer blades that can be turned and extended. They also function as outriggers for the machine.
- An electric fan automatically cools the oil when it approaches a certain temperature.
- With the fixed arm you have a stable, durable design with extra low weight.
- Turnable and extendable dozer blades that also function as outriggers for the machine.
- Low weight and short chassis make the machine easy to transport and manoeuvre in tight spaces.
- Only 78 cm wide, so it fits through all normal doorways.
- Great flexibility in terms of demolition method.
- Its low height allows the user good vision over the machine during operation, and helps give it a low centre of gravity.
- The remote control is the market's most modern and easy to use, with one-hand operation, 3.5 inch colour display and Bluetooth technology (a stable, globally certified technology that is less sensitive to interference). A sturdy harness with curved aluminium bar enhances comfort and control.
- Strong, durable baseplate is cast in one solid cast steel piece, with integrated lifting points.
- Strong LED lights provide good workplace illumination.
- The power unit's location above the undercarriage and the automatic grease pump are examples of design solutions that make the DXR 250, together with the DXR 310, the market's most easily serviced demolition robots.
- With Husqvarna's global service network you always have good access to servicing and product specialists.
- Equipped with an 18.5 kW electric motor. (22 kW electric motor available as option.)

TECHNICAL SPECIFICATION

Power	18.5/22 kW / 24.8/29.5 hp
Flow 50 / 60 Hz, l / min	65
System pressure, nominal max, Bar	200
System pressure, increased max, Bar	250
Variable flow to tools and system, l / min	0-65
Pump type	Variable load-sensing axial piston pump
Terminal	Portable remote control
Communication	Radio or cable
Radio	Industrial Bluetooth, class 1
Range, radio	Up to 100 m
Battery	High-capacity Li-ion 1600 mAh
Reach (up/forward)	4.8/4.5 m / 188.98/177.17 inch
Control system	Modular, digital CAN-based PLC
Automatic breaker lubrication	Included on standard version
Dozer blade	Included on standard version
Weight	1620 kg / 3571.43 lbs
Width, machine body, mm	780
Length, machine body, mm	1695 (incl. dozer blade)
Height, machine body, mm	1035

